

TRACTION MOTORS

Two EIMCO Model 271, 5 cylinder radial compressed air motors each developing 20 b.h.p. at 90 p.s.i. (6.33 kg/cm²)

BUCKET MOTOR

One EIMCO Model 271, 5 cylinder radial compressed air motor developing 20 b.h.p. at 90 p.s.i. (6.33 kg/cm²)

AIR REQUIREMENTS

Air Pressure Range -60 to 100 p.s.i. (4.21 to 7.03 kg/cm²)

Recommended Air Pressure -90 p.s.i. (6.33 kg/cm²)

Recommended Air Hose Size 50 mm (2")

SPECIFICATIONS

Standard Machine

Breakout force at Bucket Lip	2368 kg	5220 lb
Weight	4360 kg	9780 lb
Bucket Capacity	0.425 m ³	15 cu.ft.
Travelling speed	6.10 k.p.h.	3.50 m.p.h.

OPTIONALS

1. Solid Rubber Steel Banded Tyres.
2. Higher Discharge/ Height to 1980 mm (6'6")
Please consult Eimco Elecon for this option.
This option is not recommended with pneumatic tyres.

We reserve the right to amend, without prior notice, the information and technical data given in this specification.

EIMCO ELECON (INDIA) LTD.

Regd. Office & Works

Anand Sojitra Road, Vallabh Vidyanagar 388 120, Gujarat.

Phone : 230502, 230602, 230902. Telex : 0172-232

GRAM : EIMCON Telefax : (02692) 230067

BRANCHES

Asansol

Phone: 205901

Telex : 204-218

Bangalore

Phone: 268809,
260219

Telex : 0845-2716

Bilaspur

Phone: 5902, 3772

Telex: 0273-238

Mumbai

Phone: 221315/
221365

Telex: 011-82798

Kolkata

Phone: 292287/
294354

Telex: 021-5743

Dhanbad

Phone: 2634

Madras

Phone: 452237

Telex: 041-23323

Nagpur

Phone: 531601

Telex: 0715-479

New Delhi

Phone: 3315339/
340/341

Telex: 031-66596

Secundrabad

Phone: 844748,
846984

Telex: 042-56598